


Post-it® Fax Note	7671	Date	3/27/09	# of pages	6
To	From				
Co./Dept.	JDS Industries				
Co.	Phone #				
Phone #	Fax #				
Fax #					

Section 1: Chemical Product and Company Identification



PRODUCT: DynaSub

PRODUCT NUMBER: A2162, A2261, A2263

Section 2: Composition Information on Ingredients

Hazardous Ingredients	Ingredient Data	
#ETHYL BENZENE	% by Weight	0.14
	Cas No.	100-41-4
	Vapor Pres.	7.10mm/Hg@68F
	TLV-TWA	100ppm
	TLV-STEL	125ppm 15 Min.
	PEL-TWA	100ppm
	ORAL-LD50	3500mg/Kg Rat
	DERM-LD50	15486mg/Kg Rabbit
	INHAL-LC50	55000mg/Kg Rat-2 Hour
ISOPHORONE	% by Weight	0.28
	Cas No.	78-59-1
	Vapor Pres.	N/A/V
	TLV-TWA	N/A/V
	TLV-CEIL	5ppm
	PEL-TWA	25ppm
	ORAL-LD50	1870mg/Kg Rat
	DERM-LD50	1380mg/Kg Rabbit
	INHAL-LC50	7000mg/Kg Rat-
2-ETHYLHEXYL ALCOHOL	% by Weight	0.56
	Cas No.	104-76-7

PRODUCT: DynaSub

PRODUCT NUMBER: A2162, A2261, A2263

	Vapor Pres.	N/AV
	TLV-TWA	N/AV
	PEL-TWA	N/AV
	ORAL-LD50	7100mg/Kg Rat
	DERM-LD50	2520mg/Kg Rabbit
#2-BUTOXYETHANOL (ETHYLENE GLYCOL BUTYL ETHER)	% by Weight	1.06
	Cas No.	111-76-2
	Vapor Pres.	0.66mm/Hg@68F
	TLV-TWA	20ppm*
	PEL-TWA	50ppm*
	ORAL-LD50	470mg/Kg Rat
	DERM-LD50	220mg/Kg Rabbit
	INHAL-LC50	450ppm Rat-4 Hour
#XYLENE, MIXED ISOMERS	% by Weight	1.49
	Cas No.	1330-20-7
	Vapor Pres.	5.10mm/Hg@68F
	TLV-TWA	100ppm
	TLV-STEL	150ppm 15 Min.
	PEL-TWA	100ppm
	ORAL-LD50	4300mg/Kg Rat
	DERM-LD50	>1700mg/Kg Rabbit
	INHAL-LC50	5000ppm Rat-4 Hour
#1,2,4-TRIMETHYLBENZENE	% by Weight	10.40
	Cas No.	95-63-6
	Vapor Pres.	N/AV
	TLV-TWA	25ppm
	PEL-TWA	25ppm
	ORAL-LD50	5000mg/Kg Rat
	INHAL-LC50	18000mg/Kg Rat-4 Hour
METHYLATED M/F RESIN	% by Weight	12.48
	Cas No.	68002-20-0
	Vapor Pres.	N/AV
	TLV-TWA	N/AV
	PEL-TWA	N/AV
	ORAL-LD50	12300mg/Kg Rat
	DERM-LD50	>10000mg/Kg Rabbit
AROMATIC SOLVENT	% by Weight	20.63
	Cas No.	
	Vapor Pres.	N/AV
	TLV-TWA	100ppm
	PEL-TWA	N/AV

#This material is subject to reporting under SARA TITLE III, SECTION 313

MATERIAL SAFETY DATA SHEET

Prepared in compliance with the Federal Hazard Communication Standard 29CFR 1910.1200

PRODUCT CODE : 408-1-2W1791

PAGE: 1 of 4

SECTION I

Dyhasub

MANUFACTURER'S NAME: Specialty Finishes Company

MANUFACTURER'S ADDRESS: 15310 Arrow Blvd
Fontana, California 92335

EMERGENCY/INFORMATION: 8:00 a.m.-5:00 p.m. (909)356-1095

All Other Times (909)792-7933

(909)980-5094

TRANSPORTATION EMERGENCIES: CHEMTREC (800)424-9300

MANUFACTURER CODE IDENTIFICATION: 408-1-2W1791

CUSTOMER CODE IDENTIFICATION: 408-1-2W1791

CUSTOMER NAME: FINISHED METALS

PRODUCT NAME: NEW WHITE

PRODUCT CLASS: POLYESTER

PRODUCT TRADE NAME: SUPER SERIES 1000

PREPARATION DATE : 07/26/06

SECTION II - HAZARDOUS INGREDIENTS

OCCUPATIONAL: EXPOSURE LIMITS

ALL VALUES 8 HOUR TWA UNLESS NOTED

INGREDIENT	CAS NUMBER	ACGIH-TVL	OSHA-PEL	OTHER	UNITS	LEL	V.P.	% BY WEIGHT
Aromatic Petroleum Distillates	64742-94-5	NE	NE	100	PPM	1.0	<1.9	12.0 - 22.0
Cyclohexanone	108-94-1	25	25	NE	PPM	1.1	7.0	0.0 - 6.0
Diacetone	123-42-2	50	50	NE	PPM	1.8	0.8	0.0 - 6.0
Isobutyl Alcohol	78-83-1	50	50	NE	PPM	1.2	9.0	0.0 - 7.0
Isophorone	78-59-1	4	5-C	NE	MGCM	0.8	<1.0	0.0 - 7.0
N-butyl Acetate	123-86-4	150	150	NE	PPM	1.7	8.4	0.0 - 8.0
Xylene (Mixed Isomers)	1330-20-7	100	100	NE	PPM	1.0	5.1	0.0 - 6.0
Aluminum Hydroxide	21645-51-2	NE	NE	NE	NE	N/A	N/A	
Amorphous Silica	112926-00-8	NE	6*	NE	MGCM	N/A	N/A	
Formaldehyde	50-00-0	0.1	0.1	NE	MGCM	NDA	NDA	
Titanium Dioxide	13463-67-7	10 TOT*	10 TOT*	NE	MGCM	N/A	N/A	

This material contains ingredients covered by the California 'SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROP. 65)'

NOTES AND ABBREVIATIONS USED:

- SK : Skin absorption may potentially contribute to overall exposure
 TWA : Time weighted average
 C : Ceiling limit
 PPM : Parts per million
 MGCM : Milligrams per cubic meter
 NE : Not established
 N/A : Not applicable
 OTHER : Manufacturer recommended PEL

MATERIAL SAFETY DATA SHEET

Prepared in compliance with the Federal Hazard Communication Standard 29CFR 1910.1200

PRODUCT CODE : 408-1-2W1791

PAGE: 2 of 4

V.P. : Vapor pressure listed mm Hg @ 20 C unless otherwise noted
 NDA : No Data Available
 LEL : Lower Explosive Limit (% by volume in air)
 * : Value and hazard are for particulate (nuisance) dust which is not present in form supplied.

SECTION III - PHYSICAL DATA

BOILING RANGE : 226 - 336 | F
 VAPOR DENSITY : Heavier than air
 EVAPORATION RATE : Slower than ether
 PERCENT VOLATILE BY VOLUME : 52-54
 WEIGHT PER GALLON : 12.19-12.39 LBS./GAL.
 VOC RANGE : 3.85-4.05 LBS./GAL.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION : OSHA - COMBUSTIBLE LIQUID-CLASS II
 : DOT - COMBUSTIBLE LIQUID
 FLASH POINT : 105 | F T.C.C.

SPECIAL FIRE FIGHTING PROCEDURES: During emergency conditions, decomposition products may cause health hazard. (See reactivity data) Evacuate area of unprotected personnel. Wear self-contained breathing apparatus with full facepiece operated in the positive pressure demand mode when fighting fires. Water spray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may be moved by ventilation and ignited by heat, pilot lights, other flames, or ignition sources at locations distant from material handling point. Keep containers tightly closed and isolated from heat, electrical equipment, sparks and flame. Never use welding or cutting torch on or near container (even empty) because product (even just residue) can ignite explosively.

All five gallon or larger containers including tank cars and trucks must be grounded and/or bonded when material is transferred.

SECTION V - HEALTH HAZARD DATA

ROUTES OF EXPOSURE: Product can effect the body if it is inhaled, comes in contact with eyes or skin, or is swallowed.

EFFECTS OF OVEREXPOSURE TO PRODUCT:

EYE CONTACT: This material may cause eye irritation. Direct contact with liquid or exposure to its vapors or mists may cause burning, tearing.

MATERIAL SAFETY DATA SHEET

Prepared in compliance with the Federal Hazard Communication Standard 29CFR 1910.1200

PRODUCT CODE : 408-1-2W1791

PAGE: 3 of 4

redness, and blurred vision.

SKIN CONTACT: Prolonged and repeated contact with skin can cause defatting and drying of the skin which may result in skin irritation and dermatitis. Contact may result in skin absorption, but symptoms of toxicity are not anticipated by this route alone under normal conditions of use. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

INHALATION (BREATHING): Excessive inhalation of vapors can cause nasal and respiratory irritation. Central nervous system effects include dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even death. Respiratory symptoms associated with pre-existing lung disorders may be aggravated by exposure to this material.

INGESTION (SWALLOWING): Ingestion can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis, which can be fatal.

MEDICAL CONDITIONS THAT MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT: Pre-existing eye, skin, liver, kidney, and respiratory disorders.

EFFECTS OF CHRONIC OVEREXPOSURE AND OTHER HEALTH EFFECTS AND COMMENTS:

This product does not contain a substance that has been identified as a carcinogen or probable carcinogen by NTP.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. As a precaution, exposure to liquids, vapors, mists, or fumes should be minimized. Reports of animal test studies on one or more of the individual ingredients have shown possible effects of the liver, kidneys, lungs, and blood.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: Immediately flush eyes with water for at least 15 minutes. Hold eyelids open during the water flushing.

GET MEDICAL ATTENTION

SKIN CONTACT: Thoroughly wash exposed area with soap and water. Remove contaminated clothing and launder before re-use.

INGESTION (SWALLOWING): Do not induce vomiting. Keep person warm and quiet. **OBTAIN IMMEDIATE MEDICAL ASSISTANCE** to determine best emergency treatment. Never give anything by mouth to an unconscious person.

INHALATION (BREATHING): If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. **GET IMMEDIATE MEDICAL ATTENTION.**

SECTION VI - REACTIVITY DATA

STABILITY : Stable

HAZARDOUS POLYMERIZATION : Will not occur

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents, acids, or bases, water, reactive metals such as aluminum or magnesium, open flame, welding arcs, resistance heaters, or any other device that can result in thermal decomposition of the product.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition or burning may produce carbon monoxide, carbon dioxide, various hydrocarbons, formaldehyde, and other oxides of nitrogen.

SECTION VII - SPILL OR LEAK PROCEDURES

MATERIAL SAFETY DATA SHEET

Prepared in compliance with the Federal Hazard Communication Standard 29CFR 1910.1200

PRODUCT CODE : 408-1-2W1791

PAGE: 4 of 4

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

FOR SMALL SPILLS: Eliminate possible ignition sources. Do not flush with water. Use absorbent material, placing the contained material in an approved salvage container. Use non-sparking tools for handling the contained material.

FOR LARGE SPILLS: Eliminate possible ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Maintain adequate ventilation. Shut off source of leak or spill if safe to do so. Dike area of spill to prevent spreading and pump liquid to salvage container. Remaining liquid may be taken up with absorbent material. Place contained material in approved salvage container with non-sparking tools. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

WASTE DISPOSAL METHOD: Dispose of in accordance with all local, county, state, and federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: If workplace limit(s) of product or any component is exceeded (see Section II), use appropriate, properly fitted NIOSH/MSHA approved respirator in absence of proper environmental control (see your safety equipment supplier for proper respirator). Respiratory protection program must be in accordance with OSHA Standard 29CFR 1910.134. Engineering and administrative controls should be implemented to reduce exposure.

VENTILATION: Provide sufficient mechanical (general and/or local) ventilation to maintain exposure below TLV(s) and prevent vapor buildup.

PROTECTIVE GLOVES: Use of chemical resistant, wear resistant gloves is advised to avoid contact with the product.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised. However, OSHA regulations also may permit the use of other types of safety glasses (consult your safety equipment supplier).

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash station, safety shower, chemical resistant apron, safety shoes, and protective clothing to cover exposed areas of the body.

WORK/HYGIENIC PRACTICES: Wash hands before eating, smoking, or using the restroom. Eat only in designated areas. Smoke only in approved designated areas.

SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep away from heat, sparks, and flame. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapors. Keep containers tightly closed when not in use, and protect from moisture and foreign materials. Ground containers and equipment when pouring to avoid static discharge. Never use pressure to empty the container. The container is not a pressure vessel.

OTHER PRECAUTIONS: Do not take internally. Containers of this material may be hazardous when emptied. Since emptied containers may retain product residues (vapors, liquid, and/or solid), all hazard precautions given in this Data Sheet must be observed in handling empty containers. Dispose of container in accordance with local, county, state, and federal laws.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER NO GUARANTEE OR WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.