



## 54148CL Clear Polyester Tape

**54148CL** is a thin, conformable polyester film, single coated with a silicone pressure sensitive adhesive. Primarily used to splice silicone release coated papers, films and other difficult to bond surfaces. Also used in paint and powder coat masking applications that requires heat and chemical resistance.

### Applications

- Splicing pressure-sensitive labels, film, tape and specialty papers
- Masking for powder coating
- Sublimation

### Product Benefits

- High tack, High temperature adhesive
- Clean removal
- Chemical resistance
- Tear and break resistant

### Technical Properties

Total Thickness (not including liner)	3.3 mils
Adhesive Type	Silicone
Adhesion	35 oz/in
Tensile strength	50 lbs/in
Elongation	100%
Operating temperature	-60F - 400F
Roll length	72yds

Color	Red, Blue and Clear
<i>Values shown are typical. Certified test reports for writing specifications are available.</i>	

## Recommendations

Unwind adhesive film or tape and apply the adhesive side to the surface. Apply firm pressure. Recommended application temperature to achieve best results is 65F (18C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65F (18C) or above.

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability of fitness for a particular purpose or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the forgoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

NOTE: Innotec of WI, Inc. does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product (s) or of any final product into which the product (s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform particular purpose desired in any given situation.

**1220 Mound Avenue -Suite 140 – Racine, WI 53404 – (800) 776-7194 – (262) 637-7103 – Fax (262) 637-8205**