



# MATERIAL SAFETY DATA SHEET

PRODUCT: Paste  
REVISION NUMBER: 3

REVISION DATE: 10/30/2007  
Date Printed: 10/30/2007

## 1. PRODUCT AND COMPANY IDENTIFICATION

**MANUFACTURED BY:** TherMark Holdings, Inc.  
33 Hammond  
Suite 205  
Irvine, CA 92618  
Prod Info 323-344-9500  
CHEMTREC 800-424-9300

Use the CHEMTREC telephone number only in the event of chemical emergencies.

**PREPARED BY:** Joel Assaraf  
Chief Executive Officer

**PRODUCT CODE:** LMM14

**PRODUCT TRADE NAME:** LMM14 Black Laser Marking Paste

**CAS NO:** Mixture

**CHEMICAL FAMILY:** Decorative Coating

**PRODUCT TYPE:** Laser Marking Coating

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product does not have exposure limit values. Exposure limit values for some of the components are listed below as a guideline for safe use of this product.

### HAZARDOUS COMPONENTS

INGREDIENTS/CAS #	OSHA PEL:	ACGIH TLV:
Crystalline Silica 14808-60-7	TWA respirable dust: 0.05 mg/m <sup>3</sup>	TWA respirable fraction: 0.05 mg/m <sup>3</sup>
Iron Oxide 1309-37-1	TWA 10 mg/m <sup>3</sup>	TWA as Fe: 5 mg/m <sup>3</sup>
Nickel Compound NONE	TWA as Ni: 1.0 mg/m <sup>3</sup>	TWA as Ni: 0.2 mg/m <sup>3</sup>
Molybdenum Trioxide 1313-27-5	TWA Insoluble Mo compounds: 10.0 mg/m <sup>3</sup> Soluble Mo compounds: 3.0 mg/m <sup>3</sup>	TWA 5.0 mg/m <sup>3</sup>

## 3. HAZARDS IDENTIFICATION

**PRINCIPLE ROUTES OF EXPOSURE:** Inhalation, ingestion and dermal.

**The key immediate hazards are:**

Skin, eye, and respiratory irritant, primarily if user is exposed to dry powder and/or dust.  
May cause allergic skin and respiratory reactions.

**PRODUCT TRADE NAME: LMM14 Black Laser Marking Paste**

**Effects from Acute Exposure:**

- EYE CONTACT :** Causes eye irritation.
- SKIN CONTACT:** May cause an allergic skin reaction.
- INHALATION:** May cause an allergic respiratory reaction.
- INGESTION:** May be harmful if swallowed.

**AGGRAVATED MEDICAL CONDITIONS:**

Allergic skin and respiratory reactions.

**Effects from Chronic Exposure:**

**CARCINOGENIC INGREDIENTS:**

Nickel and certain nickel compounds: There is sufficient evidence of the carcinogenicity of nickel and nickel compounds (NTP-1985) also, (IARC 1976, vol. 11) states there is sufficient evidence for the carcinogenicity of certain nickel compounds. Nickel subsulfide is carcinogenic in rats by inhalation, producing lung cancer. Nickel compounds (nickel powder, subsulfide, oxide, carbonate, and nickelocene) produced local sarcomas in mice, rats and hamsters when given intramuscularly. Inhalation of nickel carbonyl produced a low incidence of lung tumors in rats.

This product contains greater than 0.1% crystalline silica. The International Agency for Research on Cancer (IARC) has determined that "there is sufficient evidence for the carcinogenicity of crystalline silica to experimental animals and limited evidence of carcinogenicity in humans. "The National Toxicology Program (NTP) Sixth Annual Report confirms this determination. It has listed crystalline silica as a substance reasonably anticipated to be a carcinogen.

**PRODUCT TRADE NAME: LMM14 Black Laser Marking Paste**

**OVEREXPOSURE EFFECTS:**

CONTAINS MOLYBDENUM COMPOUND(S) :

Molybdenum compounds can cause eye and respiratory irritation. They can be toxic if swallowed or inhaled based on animal studies where symptoms included anemia, loss of appetite, diarrhea, tiredness, joint pain and changes, liver and kidney damage, and lung effects.

CONTAINS NICKEL COMPOUNDS (AS REACTED INTO THE PIGMENT):

Nickel overexposure can cause allergic skin reactions and asthma. Inhalation can cause effects on the lungs such as bronchitis, emphysema, and impaired function , as well as kidney damage. Swallowing can result in nausea, vomiting, diarrhea and abdominal cramps. Chronic overexposure during nickel production has been shown to cause lung and nasal cavity cancers in workers; these effects are directly related to the degree of exposure. The compounds associated with the production environment included metallic nickel, nickel oxides and nickel sulfides. Workplaces other than those involved with mining, refining, and alloy manufacture have not been studied.

CONTAINS IRON OXIDE (AS REACTED INTO THE PIGMENT):

Long-term inhalation of iron oxide dust may lead to siderosis or iron deposition in the lung. This is not considered to be a hazardous condition.

## 4. FIRST AID MEASURES

**INGESTION:** If swallowed, give at least 3-4 glasses of water, but do not induce vomiting. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

**SKIN:** For skin contact, wash affected areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

**INHALATION:** If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

**EYES:** For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical attention if irritation develops.

**NOTES TO PHYSICIAN:** None specified.

## 5. FIRE FIGHTING MEASURES

**OSHA FLAMMABILITY CLASS:** NON-COMBUSTIBLE

**FLASH POINT:** >200 F. Not combustible. Will not burn.

**Flashpoint Method:** Pensky-Martin Closed Cup or Grabner Mini-flash

**Lower Explosive Limit:** Not Available

**Upper Explosive Limit:** Not Available

**PRODUCT TRADE NAME: LMM14 Black Laser Marking Paste**

**EXTINGUISHING MEDIA:** None required. Product will not burn.

**FIRE FIGHTING PROCEDURES:** Use water spray to cool nearby containers and structures exposed to fire.

**UNUSUAL HAZARDS:** None

## **6. ACCIDENTAL RELEASE MEASURES**

**SPILL PROCEDURES:** Wear appropriate protective equipment. Avoid the generation of dust. Collect (Vacuum, Absorb, or Shovel) material and place in closable container(s) for disposal.

## **7. HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Avoid contact with eyes, skin and clothing.

**NOTES ON HANDLING INFORMATION:** Minimize dust generation during handling. Use adequate ventilation.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**VENTILATION:** Adequate ventilation should be provided to keep particulate concentrations below acceptable Exposure Limits. Discharge from the ventilation system should comply with the applicable air pollution control regulations.

**EYE PROTECTION:** Wear safety glasses or goggles to protect against exposure.

**PROTECTIVE GLOVES:** Use gloves as a standard industrial handling procedure.

**RESPIRATORY PROTECTION:** Appropriate respiratory protection is required when exposure to airborne contaminant is likely to exceed acceptable limits. Respirators should be selected and used in accordance with OSHA Subpart I (29 CFR 1910.134) and manufacturer's recommendations.

**OTHER PERSONAL PROTECTIVE EQUIPMENT:** None specified.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Gray-yellow liquid

**BOILING POINT:** 100°C – 110°C

**VAPOR DENSITY (AIR=1):** 20 g/m<sup>3</sup>

**EVAP. RATE(BUTYL ACETATE=1):** Slower than n-Butyl Acetate

**VOC, Wt.% (EPA METH.24):** 0. Mixture contains no volatile organic compounds.

**BULK DENSITY:** 13 lb/gal (1.55 g/ml)

**SOLUBILITY (in water):** Partially soluble.

**PRODUCT TRADE NAME: LMM14 Black Laser Marking Paste**

## 10. STABILITY AND REACTIVITY

**STABILITY DATA:** STABLE

**POLYMERIZATION:** WILL NOT OCCUR

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide and depending on conditions, some hydrocarbon fragments may also be formed.

### **INCOMPATIBILITY**

**(MATERIALS TO AVOID):** Iron/ferrous containing materials. Do not store in steel, iron, tin or lined metal containers.

**CONDITIONS/HAZARDS TO AVOID:** None known.

## 11. TOXICOLOGICAL INFORMATION

No Toxicological data known.

## 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** No data at this time

**CHEMICAL FATE INFORMATION:** No data at this time.

**PERSISTENCE/DEGRADABILITY:** No data at this time.

**APPRAISAL:** No data at this time.

**MOBILITY:** No data at this time.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL OF WASTE METHOD:** Dispose in accordance with Federal, State and Local regulations.

## 14. TRANSPORT INFORMATION

**DOT Shipping Name:** NON-HAZARDOUS

**DOT HAZARD CLASS:** NONE

**DOT LABEL(S):** NONE

**UN/NA NUMBER:** NONE

**PACKING GROUP:** NONE

## 15. REGULATORY INFORMATION

**SARA SECTION 302:** None Found

**SARA (311, 312) HAZARD CLASS:** ACUTE HEALTH HAZARD

CHRONIC HEALTH HAZARD

**PRODUCT TRADE NAME: LMM14 Black Laser Marking Paste**

**SARA 313 Title III Toxic Chemical List:**

**The following chemicals are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.**

28% Molybdenum Trioxide  
<1% Metal as Manganese  
<1% Metal as Nickel

**TSCA Inventory Status:** This product (and/or all of its components) is in compliance with the U.S. EPA Toxic Substance Control Act, TSCA, (15 U.S.C. 2604).

This product and all of its components is listed on the DSL inventory.

## 16. OTHER INFORMATION

**Revisions:** The Format has been changed to meet the requirements of the new ANSI Standard Z400.1.

**LABEL INFORMATION:**

**WARNING!**

Skin, eye, and respiratory irritant.

May cause allergic skin and respiratory reactions.

Contains nickel which may cause respiratory effects, including cancer.

Avoid contact with eyes, skin and clothing.

Avoid breathing dust, mist or vapor.

Keep away from food products.

Wash thoroughly after handling and before eating, drinking or using cosmetic or tobacco products or toilet facilities.

Use with adequate ventilation.

Keep container closed when not in use.

**FIRST AID:** If inhaled, remove to fresh air. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water. Remove contaminated clothing. Get medical attention.

**IN CASE OF FIRE:** Use water, dry chemical or carbon dioxide.

**IN CASE OF SPILL:** Collect and dispose in accordance with federal, state and local regulations.

**FOR INDUSTRIAL USE ONLY.**

**DEFINITIONS AND ABBREVIATIONS :**

ACGIH = American Conference of Governmental Industrial Hygienists

C (CEIL) = The concentration that shall not be exceeded during any part of the working exposure.

CAS # = Chemical Abstracts Service Registry Number

EPA = Environmental Protection Agency

IARC = International Agency for Research on Cancer

NIOSH = National Institute for Occupational Safety and Health

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Limit

SARA = Superfund Amendments and Reauthorization Act

STEL = Short Term Exposure Limit. Usually a 15 minute time weighted average exposure.

TLV = Threshold Limit Values

TSCA = Toxic Substance Control Act

TWA = Time Weighted Average. Exposure concentration for a normal 8 hour day or 40 hour week.

VOC = Volatile Organic Content

**PRODUCT TRADE NAME: LMM14 Black Laser Marking Paste**

**DISCLAIMER:** The information contained in this Material Safety Data Sheet (MSDS) has been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No guarantee is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine the regulatory compliance obligations under any applicable federal or state laws.

**\*\*\* END OF MSDS \*\*\***