PAGE 2 OF 7 MSDS CODE: KH1 MSDS DATE: 02/22/00

MSDS REVISION DATE: 2/21/01

Plagnes

MATERIAL SAFETY DATA SHEET

SECTION I CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION: VVM59580H

Synonyms: Coated Polyester Film Chemical Family: Not Applicable

Kurz-Hastings, Inc., 10901 Dutton Road, Philadelphia, Pennsylvania 19154 Phone: Day - 215-632-2300, Night - 215-632-2309, Fax - 215-698-8130

SECTION II COMPOSITION, INFORMATION ON INGREDIENTS

MAY CONTAIN THE FOLLOWING COMPONENTS REQUIRING REPORTING BY OSHA:

COMPONENT	CAS REG. NO.	OSHA PEL TWA	CEILING	ACGIH TWA	STEL
Calcium Carbonate Carbon Black Iron Oxide Iron Oxide Iron Oxide Iron Oxide MICA (Mineral) Titanium Dioxide	1317-65-3 1333-86-4 1332-37-2 1309-37-1 12227-89-3 12001-26-2 13463-67-7	10 mg/m 3 3.5 mg/m 3 N/A 10 mg/m 3 15 mg/m 3 3 mg/m 3 10 mg/m 3	None None None None None None	5 mg/m ³ 3.5 mg/m ³ 5 mg/m ³ 5 mg/m ³ 10 mg/m ³ 3 mg/m ³	None None None None None None

All other components are considered to be non-hazardous or are present in levels below the reportable requirements under the criteria of the Federal OSHA Hazard Communication Act 29 CFR 1910.1200

SECTION III HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Spooled plastic film of various colors. Characteristic Odor. Appearance and Odor -

Statement of Hazard -Dust produced in sawing, sanding, excessive handling may be

irritating.

POTENTIAL HEALTH EFFECTS

Effects of Overexposure:

Inhalation - Material as shipped poses no health problems. Processing that could release dust such as sawing, sanding, excessive handing etc.

could result in mild respiratory irritation.

Eye Exposure - Dust may temporarily irritate eyes.

Skin Exposure - No Effect Known

- Unlikely route of exposure. Ingestion of small amounts has no Ingestion

PAGE 3 OF 7 MSDS CODE: KH1 MSDS DATE: 02/22/00 MSDS REVISION DATE: 2/21/01

MATERIAL SAFETY DATA SHEET

known effect.

POTENTIAL HEALTH EFFECTS CONTINUED

Effects of Overexposure:

Chronic (Delayed) Effects

Signs and Symptoms of Overexposure (by dust)

- None Known

- Eye or respiratory tract itching, scratching or dryness.

Carcinogenicity Determinations

No components of this product that are listed by OSHA, National Toxicology Program or IARC Monographs as carcinogens are present above 0.1%.

SECTION IV FIRST AID MEASURES

Eyes -Flush eyes with water while holding eyelids open. Consult physician if irritation persists.

Inhalation - Remove exposed person to fresh air.

Skin -Wash exposed skin areas with soap and water.

Ingestion - Not an expected route of exposure.

SECTION V FIRE FIGHTING INFORMATION

FLAMMABLE PROPERTIES

Flashpoint:

Not Applicable

Flammable Limits:

Not Applicable

Auto Ignition Temperature:

Not Applicable

Flammability Classification:

Product is combustible plastic film.

Products of Combustion:

Can include carbon monoxide, carbon dioxide and

hydrogen chloride.

FIRE FIGHTING GUIDELINES

Extinguishing Media:

Class A or B extinguishant, eg. dry chemical, foam, carbon dioxide or water. Wear respirator (pressure demand, self contained breathing apparatus, MSHA/NIOSE approved) and full protective gear for working fires.

PAGE 4 OF 7 MSDS CODE: KH1 MSDS DATE: 02/22/00

MSDS REVISION DATE: 2/21/01

MATERIAL SAFETY DATA SHEET

SECTION VI ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION

See Section VIII Below

CLEAN UP

Vacuum dust that may be generated and dispose of according to applicable federal, state and local regulations. See Section II for hazardous components.

SECTION VII HANDLING AND STORAGE

To maintain quality of material, store in cool dry atmosphere, 60° - 80° F, 40% relative humidity. No special safety precautions are necessary for storage.

SECTION VIII PROTECTION FROM OVEREXPOSURE

VENTILATION AND CONTAINMENT

Provide local exhaust ventilation that captures dust during sawing or sanding operations.

RESPIRATORY PROTECTION

If ventilation/containment measures do not reliably protect against inhalation overexposure, wear MSHA/NIOSH approved respirator suitable for protection from the dust concentrations encountered.

EYE PROTECTION

If dusty conditions are anticipated wear goggles. (ANSI 287.1-1990)

SKIN PROTECTION

Wear work gloves when handling.

OTHER PROTECTIVE MEASURES

Source of running water for cleaning skin and eyes should be available.

PERSONAL HYGIENE

Wash hands and face with soap and water efter handling and especially before eating or smoking.

CHERRY CRK WOODCRAFT

PAGE 06

KURZ-HASTINGS, INC. 10901 DUTTON ROAD PHILADELPHIA, PA. 19154

PAGE 5 OF 7 MSDS CODE: KH1 MSDS DATE: 02/22/00 MSDS REVISION DATE: 2/21/01

MATERIAL SAFETY DATA SHEET

SECTION IX PHYSICAL & CHEMICAL DATA

Appearance:

Coated Polyester Film, Various Colors

Odor:

Characteristic

Water Solubility:

Negligible

Vapor Density:

Not Applicable

Specific Gravity:

Not Applicable

Percent Volatile:

1.5% Maximum

SECTION X STABILITY AND REACTIVITY

Stability:

Stable when heated except product may become unusable (block). Prolonged

heating at elevated temperatures above 300° F can generate smoke and

acrid fumes.

Reactivity: Does not react with any common substance.

SECTIONS XI AND XII

Intentionally Omitted - Not Applicable

SECTION XIII DISPOSAL

For disposal, incinerate or landfill this material according to local, state and federal regulations. See Section II for hazardous components.

SECTION XIV TRANSPORT INFORMATION

This material is not classified by DOT as hazardous.

SECTION XV REGULATORY INFORMATION

WORK PLACE CLASSIFICATIONS

Cortain components of this material are classified as hazardous under the OSHA Hazard Communication Standard 29 CFR 1910.1200. (See Section II)

97%

PAGE 6 OF 7 MSDS CODE: KH1 MSDS DATE: 02/22/00 MSDS REVISION DATE: 2/21/01

MATERIAL SAFETY DATA SHEET

SECTION XV REGULATORY INFORMATION CONTINUED

SARA TITLE 3 SECTION 313 (40 CFR 372)

This product contains no chemicals which are listed in Section 313 above $\underline{\text{de}}$ minimis concentration.

TSCA

All components of the product are listed or are excluded from listing on the US Toxic Substances Control Act Inventory.

CALIFORNIA PROPOSITION 65

This product may contain trace levels of a component or components known to the state of California to cause birth defects or other reproductive harm:

- Toluene (108-88-3) - Mercury (7439-97-6)

This product may contain trace levels of component known to the state of California to cause cancer:

- Ethyl Acrylate (140-88-5)
- Arsenic (7440-38-2)
- Cadmium (7440-43-9)
- Nickel (7440-02-0)
- Lead (7439-92-1)
- Aniline (62-53-3)
- Formaldehyde (50-00-0)

MASSACHUSETTS RIGHT TO KNOW

The following chemicals may be present at or above the required reporting level of 0.0001%.

- Ethyl Acrylate (140-88-5)
- Vinyl Acetate (108-05-4)
- Arsenic (7440-38-2)
- Chromium (3+) (7440-47-3)
- Nickel (7440-02-0)
- Formaldehyde (50-00-0)
- Methyl Methacrylate (80-62-6)

PENNSYLVANIA RIGHT TO KNOW

The following chemicals may be present at or above reportable levels:

- Formaldehyde (50-00-0) - Chromium (3+) (7440-47-3) - Aluminum (7429-90-5)

. .

PAGE 7 OF 7 MSDS CODE: KH1 MSDS DATE: 02/22/00

MSDS REVISION DATE: 2/21/01

MATERIAL SAFETY DATA SHEET

SECTION XVI OTHER INFORMATION

REVISION SUMMARY:

MSDS has been revised to comply with ANSI 2400.1-1993.

ABREVIATIONS:

ACGIH -American Conference of Governmental Industrial Hygienists OSHA -Occupational Safety and Health Administration Threshold Limit Value TLV PEL

Permissible Exposure Limit TWA Time Weighted Average Short Term Exposure Limit Toxic Substance Control Act STEL -TSCA -

RCRA -Resource Conservation and Recovery Act

The information contained herein relates only to the specific material identified. Kurz-Hastings, Inc., believe that such information is accurate and reliable as of the date of this Material Safety Data Sheet, but no representation, guarantee or warranty, expressed or implied, is made as to the accuracy, reliability, or completeness of the information. Kurz-Hastings, Inc., urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.